

SWATHER HAULER™



Manufactured by **DUO LIFT** Mfg. Co., Inc.



Model: SW24D Swather and Windrower Trailer
Adjustable and Adaptable to Safely Carry Heavy Weight Self Propelled Swathers and Windrowers



Guide Rails Keep the Rear Tires From Turning. Railing is Adjustable for Various Tire Sizes

SPECIFICATIONS:

- **Color:**Gloss Black, Gray Wheels and White Splash Guards or Duo Lift Blue and Black Splash Guards
- **GVWR:**24,000 Lbs. Trailer is Fully D.O.T. Compliant
- **Weight:**6,050 Lbs.
- **Frame:**(2) 10" x 4" Wide Flange Beams with (3) 4" Heavy Wall Torque Tubes and (4) 4" x 4" HD Tubular Platform Supports
- **Dimensions:** Empty Transport Width 102" - Loaded Maximum Transport Width 159"
Length 30'6" Overall, Swather/Windrower Loading Area 25', Platform Height: 21"
- **Axles:**(2) 10,000 Lb. 8-Bolt Oil Bath Hubs with 5/8" Studs and 5/8" Swiveling Flange Nuts
- **Suspension:**.....(4) 5-Leaf, 5,000 Lb. Slipper Springs with Equalizers
- **Brakes:**12-1/4" x 3-1/2" Electric Brakes on Both Axles, 12-Volt Safety Breakaway System with Battery
- **Wheels:**.....(4) Hub Piloted, 17.5 x 6.75 - 8 on 6.5 Gray Color, solid Plate
- **Tires:**(4) 215/75R 17.5 LRH Radials 16-Ply, (4,850 Lbs. Cap. Each), Spare Tire Carrier Included
- **Hitch:**Gooseneck, Tapered Design, 8" x 4" Tubular Frame with Adjustable Height 2-5/16" Coupler and (2) 1/2" Safety Chains
- **Fenders:**.....14 Gauge Steel, Enclosed with Splash Guards
- **Park Stands:**.....(1) 12,000 Lb. Side-Wind, Drop Leg Jack, (4) Adjustable Height Rear Loading Jack Stands
- **Lights:**.....12-Volt, D.O.T. Stop, Turn, Tail, Marker, License Lamps, w/ 7-Way RV Trailer Electrical Connector and Wiring Enclosed in Steel Conduit or Sealed Electrical Cord
- **Platforms:** **Caster Wheel Platforms:** Slide Out type, 20" x 97" with Adjustable Platform Width, Adjustable Tire Guide Rails and Locking Pins
Drive Wheel Platforms: Folding Type, 30" x 87" with Locking Pins and Winch Operated Folding System
- **Ramps:** Slide Out, Roller Assisted, 24" x 96", Tubular with Open Angle Iron Grousers
- **Tie Downs:** (8) Strap/Chain Tie Down Locations, (4) Ratchets and (4) 2" x 27" Straps
- **Other:** D.O.T. Reflective Conspicuity Tape, HD Rear Bumper, Manual/Document Canister, Registration Holder, 17 Digit VIN Plate, Annual Federal Trailer Inspection with Inspection Certificate. Manufacturer's Certificate of Origin Furnished Upon Payment of Trailer
- **Options:** 215/75R 17.5 LRH Radial Spare Tire, Tool Box 18" x 18" x 30" Stainless Steel w/Lockable Door
- **Optional Colors:** ... Ag Green, Ag Red, Ag Yellow

DUO LIFT Manufacturing Company, Inc.

2810 38th Street • Columbus, Nebraska 68601

Phone: 402-564-8023 • FAX: 402-564-5385

Toll Free: 1-800-243-2583

Email: sales@duolift.com • Website: www.duolift.com

Authorized Dealer:



Trailer Frame

09-05-2014



SW24D Folded Transport Position



SW24D Rear View Folded Transport Position



Rear View Loading Position with Slide Out Roller Assisted Ramps



Adjustable Caster Wheel Platforms and (4) Ratchets and (4) 2" x 27" Straps per Trailer



Adjustable Position Caster Wheel Platform Railings and Wheel Stops



Winch Operated Folding Drive Wheel Platforms and Adjustable Height Loading Stands



Optional Spare Tire with Spare Tire Carrier Mounted on Gooseneck



Adjustable Height 2 5/16" Coupler, 1/2" Safety Chains Safety Breakaway System and 7-Way RV Trailer Electrical Connector