E-P TRAILERS

E-P Model 3P21K29-2B Triple Axle Trailer

SPECIFICATIONS:

Capacity..... 21,000-Lbs. GVWR @ 55 MPH
Size..... Main Deck..... 20' L x 102" W x 34" H
Sloping Afterdeck..... 48" Length
Axles..... (3) 7,000 Lb. Tubular, 8-Bolt Hub
Suspension..... Triple, 6-Leaf, 4,000 Lb. Slipper Springs
Wheels..... 16 x 6, 8B-6.5 BC, White Spoke
Tires..... (6) 235/80R16 LRE Radials, 3520-Lbs. Capacity Each
Brakes..... 12V Electric, 12 x 2, All Wheels
Coupler..... 2 5/16" Ball or 3" Pintle Ring, Adjustable Height
Park Stand..... 10K Drop-Leg, Top-Wind Jack
Safety Chains..... (2) 3/8" x 36" G70 w/Safety Hooks
Decking..... 2" Nominal Wood in Center
Side Rail..... 3/16" FL PL, 20' (Also Over Tires)
Main Frame..... W12 x 16Lb. Steel Flange Beams
Cross Members..... 4" Formed Steel Channels, 20" c-c
Afterdeck..... Angle Grousers, Self Cleaning, 10 GA Center
Fold-Up Ramps..... (2) 16 x 60 Inch, w/ Support Leg and Assist Springs
Lights..... 12V DOT LED Tail, Stop, Turn, Marker, and License Lamps with
- Way Connector and Wiring Enclosed in Steel Conduit,
Paint..... White Enamel with Epoxy Primer
Misc..... Reflective Tape, 4 x 2 Stake Pockets, 24" c-c, Rub Rails,
Splash Guards, 3" Front Deck Header
Warranty..... (1) Year Material and Workmanship



DUO LIFT® Manufacturing Company, Inc.
2810 38th St. * Columbus, NE 68601 * USA * 402-564-8681 * 402-564-8023 * FAX 402-564-5385