

SWATHER HAULER

Manufactured by **DUO LIFT** Mfg. Co., Inc.



Loading Position

Swather Hauler Trailers are Adjustable and Adaptable to Safely Carry Self Propelled Swathers and Windrowers



Folded Transport Position

Swather Hauler Folded Transport Width 102"

SPECIFICATIONS: Model: SW24D and Model: SW28D

Color: Gloss Black, Silver Wheels and White Splash Guards

GVWR: SW24D - 24,000 Lbs. OR SW28D - 28,000 Lbs., Trailers are Fully D.O.T. Compliant

Weight: SW24D - 6,050 Lbs. OR SW28D - 6,500 Lbs.

Frame: (2) 10" x 4" Wide Flange Beams with (3) 4" Heavy Wall Torque Tubes and (4) 4" x 4" HD Tubular Platform Supports

Dimensions: Folded Transport Width 102" - Loaded Maximum Transport Width 159"

Length 30'6" Overall, Swather/Windrower Loading Area 25', Platform Height: 21"

Axles: SW24D - (2) 10,000 Lb. OR SW28D (2) 12,000 Lb. 8-Bolt Oil Bath Hubs with 5/8" Studs and 5/8" Swiveling Flange Nuts

Suspension: SW24D - (4) 5-Leaf, 5,000 Lb. OR SW28D (4) 6-Leaf, 6,000 Lb. Slipper Springs with Equalizers

Brakes: SW24D - 12-1/4" x 3-1/2" Electric Brakes on Both Axles, 12-Volt Safety Breakaway System with Battery
SW28D - 12-1/4" x 5" Electric Brakes on Both Axles, 12-Volt Safety Breakaway System with Battery

Wheels: (4) Hub Piloted, 17.5 x 6.75 - 8 on 6.5 Silver Color, Solid Plate

Tires: SW24D - (4) 215/75R 17.5 LRH Radials 16-Ply, (4,850 Lbs. Cap. Each), Spare Tire Carrier Included
SW28D - (4) 235/75R 17.5 LRH Radials 16-Ply, (6,000 Lbs. Cap. Each), Spare Tire Carrier Included

Hitch: Gooseneck, Tapered Design, 8" x 4" Tubular Frame with Adjustable Height 2-5/16" Coupler and (2) 1/2" Safety Chains

Fenders: 14 Gauge Steel, Enclosed with White Splash Guards

Park Stands: (1) 12,000 Lb. Side-Wind, Drop Leg Jack, (4) Adjustable Height Rear Loading Jack Stands

Lights: 12-Volt, D.O.T. Stop, Turn, Tail, Marker, License Lamps, w/ 7-Way RV Trailer Electrical Connector and Wiring Enclosed in Steel Conduit or Sealed Electrical Cord

Platforms: **Caster Wheel Platforms:** Patent Pending Slide Out Type, 45" x 92" Tread Plate Platforms with Bolt-On Multi Position Caster Wheel Angling Guide/Stops, Locking Pins and Tire Guide Rails. Accommodates Caster Wheel Width From 108" to 129". Allows Caster Wheels to Spin to the Forward Travel Position During Unloading.

Ramps: **Drive Wheel Platforms:** Folding Type, 30" x 87" with Locking Pins and Spring Lift Assist Folding System

Tie Downs: Slide Out, Roller Assisted, 24 1/2" x 102", Tubular w/Open Angle Iron Grousers & Tapered Ramp Edge

Other: (8) 5/8" x 3" x 3" D-Ring Chain Tie Down Location

D.O.T. Reflective Conspicuity Tape, HD Rear Bumper, Manual/Document Canister, Registration Holder, 17 Digit VIN Plate, Annual Federal Trailer Inspection with Inspection

Options: Certificate. Manufacturer's Certificate of Origin Furnished Upon Payment of Trailer

Optional Colors: Radial Spare Tire, Tool Box 18" x 18" x 30" Stainless Steel w/Lockable Door
Ag Green, Ag Red, Ag Yellow and Duo Lift Blue

DUO LIFT Manufacturing Company, Inc.

Authorized Dealer:



Trailer Frame

2810 38th Street • Columbus, Nebraska 68601

Phone: 402-564-8023 • FAX: 402-564-5385

Toll Free: 1-800-243-2583

Email: sales@duolift.com • Website: www.duolift.com

7-1-2015



Swather Hauler Trailers are Adjustable and Adaptable to Safely Carry Self Propelled Swathers and Windrowers



Windrowers can be Loaded without a Header



Header Rest Supports

Rear View Loading Position with Slide Out Roller Assisted Ramps and Ramp Widening Rails



SW24D Folded Transport Position 102"



Patent Pending Slide Out Caster Wheel Rotation and Support Platforms with Adjustable Position Tire Angling / Stop Guides



Rear View Folded Transport Position Dual Spring Lift Assist for folding each Drive Wheel Platform



Loading a 16' Rotary Disc Windrower



Loaded 16' Rotary Disc Windrower



Unloading a 16' Sickle Windrower