


TD1625

TANDEM AXLE

Standard Features

CAPACITY	20,000 LBS. G.V.W.R.
SUSPENSION	2" WIDE X 8-LEAF UNDERSLUNG SLIPPER SPRINGS, 5,000 LBS. CAPACITY EACH
AXLES	3" X 3" X .375" HEAVY WALL TUBING
SPINDLES	2.50" DIA. 1144 COLD ROLLED SHAFT
HUBS	819, 8-BOLT ON 8" BOLT CIRCLE, 5,790 LBS. CAP. EA.
WHEELS	16.1" X 11" X 8 - 8", 6,000 LBS. CAP. EACH, SILVER
TIRES	PRICED SEPARATELY, SEE BELOW
BRAKES	TWO-WHEEL FREE-BACKING HYDRAULIC SURGE
FRAME	7" STRUCTURAL CHANNEL
JACK	10,000 LB. TOP-WIND DROP-LEG
LIGHTS	STOP / TURN / TAIL FUNCTION RED LED LIGHTS WITH 7-WAY RV CONNECTOR
HITCH	ADJUSTABLE HEIGHT CLEVIS
OTHER	(2) D.O.T. SAFETY CHAINS PLATFORM IN TONGUE FOR PUMP (5) HOSE STORAGE HOOKS (4) 6" WIDE CROSS MEMBERS (2) 12" X 12" FILL STEPS CONSPICUITY TAPE

Tire and Wheel Options

- 16.5 X 16.1 10-PLY TUBELESS IMPLEMENT, NEW 11:00 X 22.5 HIGHWAY TIRES, GOOD USED
- 11:00 X 22.5 TRUCK TIRES, 22.5 X 8.25 X 8-8 WHEELS

Brake Options

- 2-WHEEL OR 4-WHEEL ELECTRIC BRAKES

Hitch Options

- BALL COUPLER OR LUNETTE

Other Options

- WALK-ON FENDERS, CHEMICAL INDUCTOR STAND, HOSE STORAGE STAND, EXTRA FRAME LEGTH AND
- PLATFORM TO ACCOMMODATE CHEMICAL STORAGE CONTAINERS, ATV ETC...

