



## Standard Eestures

| Stand | lard | Features |
|-------|------|----------|
|-------|------|----------|

|                         | BW208   | BW212                      |  |
|-------------------------|---|----------------------------|--|
| CAPACITY                | 28,000 LBS. GVWR  | 32,000 LBS. GVWR           |  |
| CAFACITY                | UP TO 8 LARGE ROUND BALES   | UP TO 12 LARGE ROUND BALES |  |
| WAGON WEIGHT            | 4,400 LBS.  | 5,000 LBS.                 |  |
| OVERALL WAGON<br>LENGTH | 32'4"   | 34'10"                     |  |
| BALE CRADLE WIDTH       | 124.5"  | 124.5"                     |  |
| FRONT TRACK WIDTH       | 60"   | 60"                        |  |
| REAR TRACK WIDTH        | 92"   | 92"                        |  |
| HUBS, 8-BOLT            | (2) 819, (2) 886  | (4) 886                    |  |
| SPINDLES                | FRONT: 2.5" - REAR: 3"  | FRONT: 3" - REAR: 3"       |  |
| WHEELS                  | (4) 22.5" X 11.75", 8-BOLT SILVER/GRAY HD SPOKE WHEELS  |                            |  |
| TIRES                   | (4) 385/65R22.5 USED SUPER SINGLE TIRES   |                            |  |
| LIGHTS                  | AG LIGHT PACKAGE WITH 7-WAY RV CONNECTOR AND LED LIGHTS   |                            |  |
| FRONT AXLE              | 8" X 4" HEAVY WALL TUBING WITH 2.75" DIAMETER ROCKING PIN AND SEAMLESS (DOM) BUSHING  |                            |  |
| MAIN FRAME              | (2) 10" X 4" - 22# WIDE FLANGE BEAMS WITH (1) 6" HEAVY WALL TORQUE TUBE AND FRONT<br>ROLL GUARD   |                            |  |
| STEERING                | 5TH WHEEL WITH 2" SAE HEATED TREATED, 75 TON SEMI KING PIN WELDED TO 20" DIAMETER TURNTABLE   |                            |  |
| BALE CRADLES            | (3)120" ON BW208 (4)120" AND (1) 60" ON BW208 & BW212. ALL CRADLES MADE WITH 3.5"<br>HEAVY WALL ROUND TUBE  |                            |  |
| GOOSENECK               | DOUBLE 8" X 4" HEAVY WALL RECTANGULAR TUBE  |                            |  |
| TONGUE                  | 4" X 3" HEAVY DUTY TUBING, 78" LENGTH WITH (2) GRADE 70, 1/2" X 40" SAFETY CHAINS WITH LOAD RATING TAGS   |                            |  |
| REAR HITCH              | 1/2" THICK AND REINFORCED REAR HITCH PLATE WITH (2) SAFETY CHAIN HOOK LOCATIONS   |                            |  |
| PAINT                   | TWO PART GLOSS BLACK, ACID ETCH STEEL PREP., ALL WELD SLAG AND SCALE REMOVED PRIOR TO PAINTING, SILVER/GRAY WHEELS, RED, ORANGE AND YELLOW AG REFLECTIVE CONSPICUITY TAPE |                            |  |
| OPTIONS                 | AG TRANSPORT LIGHT PACKAGE, HYDRAULIC SURGE BRAKES, HEAVY DUTY EXTENSION TONGUE, SINGLE OR DOUBLE SPRING LIFT ASSIST  |                            |  |
| WARRANTY                | (5) YEAR MAIN FRAME WARRANTY, (1) YEAR COMPONENT WARRANTY, AS IS USED TIRES   |                            |  |

