



DC6050

CONE BOTTOM

TRANSPORT TRAILER

Standard Features

CAPACITY	4,000 LBS. TRANSPORT
ACCOMMODATES	(2) 2,500 OR (2) 3000-GALLON CONE BOTTOM, 15° SLOPE TANKS FOR PORTABLE FIELD STORAGE (TANKS NOT INCLUDED)
SPINDLES	2" DIA. 1144 COLD ROLLED SHAFT
HUBS	611, 6-BOLT CIRCLE, 3,600 LBS. CAP. EA.
WHEELS	15" X 6" X 6 - 6", SILVER
TIRES	225/75R15D RADIAL TIRE, 2,540 LBS CAP. EA.
FRAME	6" STRUCTURAL CHANNEL
JACK	2,000 LB. TOP WIND
LIGHTS	STOP / TURN / TAIL FUNCTION RED LED LIGHTS WITH 7-WAY RV CONNECTOR
HITCH	ADJUSTABLE HEIGHT CLEVIS
STORAGE POSITION	SITE FILL ONLY
LIFT	MANUAL HYDRAULIC PUMP WITH (2) LIFT CYLINDERS

DIMENSIONS	LENGTH.....21' WIDTH.....8' HEIGHT WITH 2500 GAL. TANK151" HEIGHT WITH 3000 GAL. TANK171"
OTHER	(2) D.O.T. SAFETY CHAINS PLATFORM IN TONGUE FOR PUMP (2) HOSE STORAGE HOOKS PER CONE (4) TANK TIE DOWNS
MISC.	CONSPICUITY TAPE

Available Options

- BALL COUPLER OR LUNETTE EYE
- HIGHWAY SPEED SPINDLES, 6-BOLT HUBS WITH 225/75R15 TIRES ON WHITE
- SPOKE WHEELS
- HOSE STAND

DC6050 TRAILER MUST BE TRANSPORTED WITH EMPTY TANKS.

