



## DS1750E ECONOMY

# DUO STEER TRAILER

The DS1750E Duo Steer Wagon by Duo Lift is a versatile tool designed for use behind fertilizer applicator bars, row crop planters, air seeders, and more. It features 4-wheel steering and a manual locking system, allowing you to switch between a fixed rear axle position for road use and a steerable position for field operations by adjusting the steering tie rod assembly. This robust wagon is equipped with 18.4" x 26" lug tires and a 1750-gallon cone-bottom tank, making it durable and efficient for heavy-duty tasks.

### Standard Features

<b>CAPACITY</b>	32,000 LBS. G.V.W.R.
<b>MAIN FRAME</b>	8" X 3" HEAVY WALL TUBING
<b>TANK</b>	(1) WHITE POLY, 1750 GALLON, CONE BOTTOM
<b>TRACK WIDTH</b>	120" FIXED TRACK
<b>WHEEL BASE</b>	9' 10"
<b>HUBS</b>	886, 8-BOLT, 8,000 LB CAPACITY, EACH
<b>TIRES AND WHEELS</b>	<ul style="list-style-type: none"> <li>• 18.4 X 26 10-PLY ON</li> <li>• 26 X D-16, 8-BOLT</li> <li>• 12,000-LBS. CAP. EACH</li> </ul>
<b>REAR AXLE</b>	7" X 5" HEAVY WALL TUBING
<b>FRONT AXLE</b>	7" X 5" X HEAVY WALL TUBING WITH 2.75" DIA. ROCKING PIN AND SEAMLESS (DOM) BUSHING
<b>SPINDLES</b>	3" DIAMETER 1144 SHAFT, PLACED ON BOTTOM OF AXLE TUBE
<b>LIGHTS</b>	AG LIGHT PACKAGE, WITH 7-WAY RV CONNECTOR
<b>AXLE CLEARANCE</b>	28" WITH STANDARD TIRES
<b>STEERING</b>	FRONT: 5TH WHEEL WITH 2" SAE, HEAT TREATED, 75-TON SEMI-KING PIN TURNTABLE, 20" DIA. PLATES REAR: 5TH-WHEEL TURNTABLE WITH (2) 20" DIA. PLATES, CONNECTED TO A TIE ROD FOR 4-WHEEL STEER
<b>LOCK SYSTEM</b>	MANUAL LOCK WITH TIE ROD POSITIONING
<b>TANK SUPPORTS</b>	CRADLE FOR 1750 GALLON CONE BOTTOM TANK
<b>GREASE</b>	GREASE FITTINGS THROUGHOUT ENTIRE WAGON
<b>TONGUE</b>	8' HEAVY-DUTY PULL PIN EXTENSION TONGUE WITH DOUBLE SPRING LIFT ASSIST, (2) DOT 1/2" X 40" SAFETY CHAINS, ACCEPTS 1" HITCH PIN
<b>COLOR</b>	FRAME: BLACK WAGON FRAME, SILVER WHEELS TANK: LIGHT BLUE OR OPTIONAL BLUE, BLACK OR YELLOW



DS1750E SHOWN WITH 1750-GALLON WHITE POLY CONE BOTTOM TANK



**DS1750E ECONOMY**

# DUO STEER TRAILER

**DETAIL SHOTS**

