

LBITXLB

LOW BOY WAGON



Specifications

GVWR	32,000 LBS
TANK CAPACITY	(2) 1,000 OR 1,450 GALLON, NH3 TANKS
TRACK WIDTH	FRONT: TRACK WIDTH 60" REAR: ADJUSTABLE TRACK WIDTH 92" - 120"
HUBS	886 HUBS, 8-BOLT WITH 8,000 LBS CAPACITY EACH
WHEELS	22.5 X 11.75 8-BOLT, ON 8" BOLT CIRCLE 8,000 LB CAPACITY
TIRES	385/65 R 22.5 USED SUPER SINGLE
SPINDLES	3" DIAMETER 1144 SHAFT
FRONT AXLE	4" X 8" HEAVY WALL TUBING WITH 2.75" DIAMETER, ROCKING PIN AND SEAMLESS (DOM) BUSHING
STEERING	5TH WHEEL WITH 2" SAE, HEAT TREATED 75 TON SEMI KING PIN TURNABLE, 20" DIAMETER
MAIN FRAME	10" WIDE-FLANGE STEEL BEAMS AND 6" SCHEDULE 80 ROUND TORQUE TUBE
TANK SUPPORTS	(2) ADJUSTABLE TANK MOUNTING PADS TO ACCOMMODATE TWIN 1,000 OR 1,450 NH3 TANKS
GOOSE NECK	GOOSE NECK - DOUBLE 4" X 8" HEAVY WALL RECTANGULAR TUBE
TONGUE	HEAVY DUTY EXTENSION TONGUE WITH (2) D.O.T. 1/2" X 40" SAFETY CHAINS, DOUBLE SPRING LIFT ASSIST, ID TAG
MISCELLANEOUS	NH3 HOSE ROUTING BRACKETS, REMOVABLE FRONT MOUNTING PLATE WITH (3) 1-1/4" SCHEDULE 80 NH3 COUPLINGS INSTALLED, ROLL BAR ON FRONT OF GOOSE NECK, AG CONSPICUITY TAPE
LIGHTS	STOP TURN TAIL FUNCTION WITH 7-WAY RV CONNECTOR

Available Options

- BOLT-ON SIDE PLATFORM
- BOLT-ON FRONT STEEL MESH WALKWAY
- BRAKE LOCK OUT
- 425/65 R 22.5 USED SUPER SINGLE TIRES
- OPTIONAL PAINT COLORS
- BOLT ON TANK LEG CRADLE ASSEMBLY



ADJUSTABLE REAR AXLE



ADJUSTABLE TANK MOUNTING PADS



BOLT-ON CATWALK

