



N2200

HI-RISE WAGON

Standard Features

CAPACITY	20,000 LBS. G.V.W.R. (2) 1,000 GALLON NH3 TANKS 108" OR 120" TANKS
TRACK WIDTH	120" NON-ADJUSTABLE
WHEEL BASE	120"
AXLE CLEARANCE HUBS	APPROX. 30" W/ 16.5L X 16.1 TIRES 819, 8-BOLT ON 8" BOLT CIRCLE, 5,790 LBS. CAP. EA. 5,790 LBS. CAPACITY EACH
WHEELS	16.1" X 11" X 8 - 8", 6,000 LBS. CAPACITY EACH, SILVER
SPINDLES	2.50" DIA. 1144 COLD ROLLED SHAFT
AXLES FRONT BOLSTER	8" X 4" HEAVY WALL TUBING HEAVY DUTY ROCKING FRONT BOLSTER WITH GREASED 2" DIA. ROCKER PIN
STEERING	5TH WHEEL W/ 9/16" X 20" DIA. CIRCULAR DISCS W/ 2" DIA. KING PIN

OTHER	4" X 3" TONGUE WITH (2) 1/2" X 40" DOT SAFETY CHAINS W/ HOOK & LATCH, CONSPICUITY TAPE
LIGHTS	STANDARD

Available Options

- BRAKES: ELECTRIC OR HYDRAULIC
- LIGHTS: SEALED BEAM, WIRING IN CONDUIT
- 15" OFFSET TONGUE - RIGHT OR LEFT

Tire Options

- 16.5L X 16.1 14-PLY IMPLEMENT RIB
- 21.5L X 16.1 10-PLY IMPLEMENT RIB
- 21.5L X 16.1 14-PLY IMPLEMENT RIB385/65R22.5 USED
SUPER SINGLE

Used Truck Tires

- 385/65R22.5 USED SUPER SINGLE
- 425/65R22.5 USED SUPER SINGLE
- 445/50R22.5 USED SUPER SINGLE
- 445/65R22.5 USED SUPER SINGLE

