

SWATHER HAULERS

Standard Features

	SW25D, SW25HD	SW28D, SW28HD	SW30D, SW30HD, SW30XD, SW30XHD
GVWR:	25,000 LBS. TRAILER IS FULLY D.O.T. COMPLIANT	28,000 LBS. TRAILER IS FULLY D.O.T. COMPLIANT	30,000 LBS. TRAILER IS FULLY D.O.T. COMPLIANT
CAPACITY:	SELF PROPELLED SWATHERS AND WINDROWERS UP TO 18,000 LBS. (THE TOWING VEHICLE MUST BE RATED TO TOW THE GROSS TRAILER WEIGHT OF THE SWATHER HAULER TRAILER)	SELF PROPELLED SWATHERS AND WINDROWERS UP TO 20,000 LBS. (THE TOWING VEHICLE MUST BE RATED TO TOW THE GROSS TRAILER WEIGHT OF THE SWATHER HAULER TRAILER)	SELF PROPELLED SWATHERS AND WINDROWERS UP TO 22,000 LBS. (THE TOWING VEHICLE MUST BE RATED TO TOW THE GROSS TRAILER WEIGHT OF THE SWATHER HAULER TRAILER)
WEIGHT:	7,000 LBS.	7,500 LBS.	8,500 LBS
FRAME:	(2) 10" X 4" WIDE FLANGE BEAMS WITH (3) 4" HEAVY WALL TORQUE TUBES AND (4) 4" X 4" HD TUBULAR PLATFORM SUPPORTS		
DIMENSIONS:	EMPTY TRANSPORT WIDTH 102" - LOADED MAXIMUM TRANSPORT WIDTH 159" - LENGTH 31' OVERALL SWATHER/WINDROWER LOADING AREA 18', PLATFORM HEIGHT: 21"		EMPTY TRANSPORT WIDTH 102" - LOADED MAXIMUM TRANSPORT WIDTH 159" - LENGTH 32' OVERALL SWATHER/WINDROWER LOADING AREA 18', PLATFORM HEIGHT: 21"
AXLES:	(2) 10,000 LB. 8-BOLT OIL BATH HUBS WITH 5/8" STUDS AND 5/8" SWIVELING FLANGE NUTS	(2) 12,000 LB. 8-BOLT OIL BATH HUBS WITH 5/8" STUDS AND 5/8" SWIVELING FLANGE NUTS	(2) 15,000 LB. 8-BOLT OIL BATH HUBS WITH M22 STUDS AND M22 SWIVELING FLANGE NUTS
SUSPENSION:	(4) 5-LEAF, 5,000 LB. SLIPPER SPRINGS WITH EQUALIZERS	(4) 6-LEAF, 6,000 LB. SLIPPER SPRINGS WITH EQUALIZERS	(4) 8-LEAF, 10,000 LB. SLIPPER SPRINGS WITH EQUALIZERS
BRAKES:	12-1/4" X 3-3/8" ELECTRIC BRAKES ON BOTH AXLES, 12-VOLT SAFETY BREAKAWAY SYSTEM WITH BATTERY		
WHEELS:	(4) HUB PILOTED, 17.5 X 6.75 - 8 ON 6.5 SILVER COLORED, SOLID PLATE		(8) HUB PILOTED, 17.5 X 6.75 - 8 ON 275MM SILVER COLOR, DUAL WHEELS
TIRES:	(4) 215/75R 17.5 LRH RADIALS 16-PLY, (4,805 LBS. CAP. EACH), SPARE TIRE CARRIER INCLUDED	(4) 235/75R 17.5 LRH RADIALS 16-PLY, (6,005 LBS. CAP. EACH), SPARE TIRE CARRIER INCLUDED	(8) 215/75R 17.5 LRH RADIALS 16-PLY, (4,540 LBS. CAP. EACH), SPARE TIRE CARRIER INCLUDED
HITCH:	GOOSENECK, TAPERED DESIGN, 8" X 4" TUBULAR FRAME WITH 30,000 LB. ADJUSTABLE HEIGHT 2-5/16" COUPLER AND (2) 1/2" SAFETY CHAINS		
FENDERS:	14 GAUGE STEEL, ENCLOSED WITH WHITE SPLASH GUARDS, 80" X 16" - OUTSIDE TO OUTSIDE 82"	14 GAUGE STEEL, ENCLOSED WITH WHITE SPLASH GUARDS	14 GAUGE STEEL, ENCLOSED WITH WHITE SPLASH GUARDS, 80" X 24" - OUTSIDE TO OUTSIDE 82"
PARK STANDS:	(1) 12,000 LB. SIDE-WIND, DROP LEG JACK, (2) ADJUSTABLE HEIGHT REAR LOADING JACK STANDS		
LIGHTS:	12-VOLT, D.O.T. STOP, TURN, TAIL, MARKER, LICENSE LAMPS, W/ 7-WAY RV TRAILER ELECTRICAL CONNECTOR AND WIRING ENCLOSED IN STEEL CONDUIT OR SEALED ELECTRICAL CORD		
PLATFORMS:	CASTER WHEEL PLATFORMS: PATENT PENDING SLIDE OUT TYPE, 46" X 98" TREAD PLATE PLATFORMS WITH BOLT-ON MULTI POSITION CASTER WHEEL ANGLING GUIDE/STOPS, LOCKING PINS AND TIRE GUIDE RAILS. ACCOMMODATES CASTER WHEEL TRACK WIDTH FROM 108" TO 129". ALLOWS CASTER WHEELS TO SPIN TO THE FORWARD TRAVEL POSITION DURING UNLOADING. DRIVE WHEEL PLATFORMS: FOLDING TYPE, 30" X 88" WITH LOCKING PINS, SPRING LIFT ASSIST FOLDING SYSTEM AND REMOVABLE TIRE GUIDE RAILS		
RAMPS:	SLIDE OUT, ROLLER ASSISTED, 24 1/2" X 102", TUBULAR WITH OPEN ANGLE IRON GROUSERS AND TAPERED RAMP EDGE		
TIE DOWNS:	(8) 5/8" X 3" X 3" D-RING CHAIN TIE DOWN LOCATIONS		
OTHER:	D.O.T. REFLECTIVE CONSPICUITY TAPE, HD REAR BUMPER, RAMP LIFTING TOOL, MANUAL/DOCUMENT CANISTER, REGISTRATION HOLDER, 17 DIGIT VIN PLATE, ANNUAL FEDERAL TRAILER INSPECTION W/ INSPECTION CERTIFICATE. MANUFACTURER'S CERTIFICATE OF ORIGIN FURNISHED UPON PAYMENT OF TRAILER		
COLOR	BLACK		



SWATHER HAULERS



FOLDED TRANSPORT POSITION USING DUAL SPRING LIFT ASSIST FOR FOLDING ALL PLATFORMS. OPTIONAL 801158 STROBE LIGHT PACKAGE



REAR HITCH IS INCLUDED ON THE SW25HD, SW30HD AND SW30XHD MODELS



LOADING A 16' SP WINDROWER ON A SW30XD



RAMP LIFTING TOOL, NOW STANDARD



WINDROWERS CAN BE LOADED WITHOUT A HEADER



FOLDING CASTER WHEEL ROTATION AND SUPPORT PLATFORMS WITH ADJUSTABLE POSITION TIRE ANGLING GUIDE STOPS



LOADED 16' ROTARY DISC WINDROWER ON A SW25D



REAR VIEW LOADING POSITION WITH SLIDE OUT ROLLER ASSISTED RAMPS

