


TC9075

CONE BOTTOM

TRANSPORT TRAILER

CAPACITY	7,000 LBS. TRANSPORT
ACCOMMODATES	(3) 2,500 OR (3) 3,000 GALLON CONE BOTTOM, 15° SLOPE TANKS FOR PORTABLE FIELD STORAGE. TANKS NOT INCLUDED
SPINDLES	2" DIAMETER 1144 COLD-ROLLED SHAFT
HUBS	611, 6-BOLT CIRCLE, 3,600 LBS. CAPACITY EACH
WHEELS	16" X 16" X 6-6", SILVER SPOKE
TIRES	235/80R16 E-PLY RADIAL TIRE, 3,520 LBS CAPACITY EACH
FRAME	6" STRUCTURAL CHANNEL
JACK	2,000 LB. TOP-WIND
LIGHTS	AG TRANSPORT LIGHTS
HITCH	ADJUSTABLE HEIGHT CLEVIS
DIMENSIONS	LENGTH - 31' WIDTH - 8' RAISED POSITION: HEIGHT WITH 2500 GAL. TANK - 151" RAISED POSITION: HEIGHT WITH 3000 GAL. TANK - 171"
OTHER	(2) D.O.T. SAFETY CHAINS, PLATFORM IN TONGUE FOR PUMP, (2) HOSE STORAGE, HOOKS PER CONE, (2) HOLD DOWNS PER CONE AND CONSPICUITY TAPE
LIFT	MANUAL HYDRAULIC PUMP WITH (2) LIFT CYLINDERS



Available Options

- BALL COUPLER OR LUNETTE EYE
- HIGHWAY SPEED SPINDLES, 6-BOLT HUBS WITH 235 TIRES ON WHITE SPOKE WHEELS
- HOSE STAND

TC9075-30 TRAILER MUST BE TRANSPORTED WITH EMPTY TANKS.



PHONE: (800) 243-2583 EMAIL: SALES@DUOLIFT.COM

WEB: WWW.DUOLIFT.COM

Effective 2/8/23