

TD1200CB, TD1200SCB STRETCH CONE BOTTOM TRAILERS



TD1200CB



TD1200SCB STRETCH

Specifications

GVWR	16,000 LBS. G.V.W.R.
TANK	ACCOMMODATES 1200 GALLON CONE BOTTOM TANK
SUSPENSION	6-LEAF X 2" UNDER SLUNG SLIPPER SPRING
AXLE	3" X 3" X 1/4" SQUARE TUBING
SPINDLES	2-1/4" 1144 COLD ROLLED SHAFT
HUBS	6-BOLT 4570 LBS. CAPACITY EACH
WHEELS & TIRES	16 X 6 - 6-BOLT, 235 TIRE
TRACK WIDTH	75" CENTER OF TIRE TO CENTER OF TIRE
FRAME	7" STRUCTURAL CHANNEL
FENDER	10.314 X 72 TEARDROP
STEP	FILL STEPS AND PLATFORM WITH SAFETY RAILING
JACK	2,000 LB. TOP WIND
HITCH	ADJUSTABLE HEIGHT CLEVIS
LIGHTS	STANDARD
SAFETY CHAINS	TWO D.O.T. 3/8" X 40" CHAINS WITH I.D. TAG AND RETAINER LATCH
MISC	CONSPICUITY TAPE, HOSE STORAGE HOOK , SAFETY SIGNS INSTALLED,AND OWNERS MANUAL ATTACHED
WARRANTY	5-YEAR WARRANTY ON MANUFACTURED PRODUCTS

Available Options

TIRES	12.5L X 15, 10-PLY, 235/80R16 LRE
BRAKES	2-WHEEL OR 4-WHEEL HYDRAULIC OR ELECTRIC
HITCH	2-5/16" ADJUSTABLE HEIGHT BALL COUPLER OR 3" LUNETTE EYE
HOSE STAND	BOLT ON
INDUCTOR STAND	BOLT ON FOR 15 GAL. INDUCTOR TANK
JACK	10,000 LB. DROP LEG TOP WIND
TANK	1200 GALLON CONE BOTTOM TANK
D.O.T. COMPLIANT PKG	MEETS CFR 49 CODE
OTHER	CUSTOM REQUIREMENTS AVAILABLE

