



CONE BOTTOM

TANDEM AXI E TRAIL FRS

IANDEM AXLE TRAILERS	
CAPACITY:	16,000 LBS. G.V.W.R.
SUSPENSION:	6-LEAF X 2" UNDERSLUNG SLIPPER SPRINGS
AXLES:	3" X 3" X .250" SQUARE TUBING / 75" TRACK
	WIDTH
SPINDLES:	2" DIAMETER 1144 COLD ROLLED SHAFT
HUBS:	8-BOLT, HIGH SPEED 8, ON 6.5" WHEELS
WHEELS:	16" X 6" X 8 BOLT ON - 6.5" HIGH SPEED SILVER MOD WHEELS
TIRES:	235/80R16 LRE
FRAME:	7" STRUCTURAL CHANNEL
DIMENSIONS:	CB LENGTH - 173" SCB LENGTH - 257
STEP:	FILL STEP WITH SAFETY RAILING
FENDERS:	10.75" X 72 TEAR DROP WITH SPRAY-ON PRO-
FENDERS:	TECTIVE COATING
TANK:	ACCOMMODATES 1200 GAL. OR 1300 GAL. CONE BOTTOM TANK
	(TANK NOT INCLUDED)
LIGHTS:	STOP / TURN / TAIL FUNCTION RED LED
	LIGHTS WITH 7-WAY RV CONNECTOR
JACK:	2,000 LB. TOP-WIND
нітсн:	ADJUSTABLE HEIGHT CLEVIS
OTHER:	(2) DOT SAFETY CHAINS, (5) HOSE STORAGE HOOKS, CONSPICUITY TAPE, SAFETY SIGNS, OWNERS MANUAL, (2) ACE TANK HOLD DOWNS





Available Options

- FREE-BACKING HYDRAULIC SURGE BRAKES
- ELECTRIC BRAKES WITH SAFETY BREAKAWAY KIT
- BALL COUPLER OR LUNETTE EYE
- HIGHWAY SPEED SPINDLES, 6-BOLT HUBS WITH 235 TIRES ON WHITE SPOKE WHEELS
- HOSE STAND
- INDUCTOR STAND
- HIGHER CAPACITY TOP-WIND JACKS
- ENDURAPLAS 1200 GALLON TANK HOLD DOWNS ILO ACE TANK HOLD DOWNS





PHONE: (800) 243-2583 EMAIL: SALES@DUOLIFT.COM