


TD1610

TANDEM AXLE

Standard Features

CAPACITY	20,000 LBS. G.V.W.R.
SUSPENSION	2" WIDE X 8-LEAF UNDERSLUNG SLIPPER SPRINGS, 5,000 LBS. CAPACITY EACH
AXLES	3" X 3" X .375" HEAVY WALL TUBING
SPINDLES	2.50" DIA. 1144 COLD ROLLED SHAFT
HUBS	819, 8-BOLT ON 8" BOLT CIRCLE, 5,790 LBS. CAP. EA.
WHEELS	22.5" X 8.25" X 8 - 8", 6,000 LBS. CAP. EA., SILVER
TIRES	PRICED SEPARATELY, SEE BELOW
BRAKES	TWO-WHEEL FREE-BACKING HYDRAULIC SURGE

FRAME	7" STRUCTURAL CHANNEL
JACK	10,000 LB. TOP-WIND DROP-LEG
DIMENSIONS	FRAME WIDTH, 74 INCHES OVERALL LENGTH, 17 FEET
LIGHTS	STOP / TURN / TAIL FUNCTION RED LED LIGHTS WITH 7-WAY RV CONNECTOR
HITCH	ADJUSTABLE HEIGHT CLEVIS
OTHER	(2) D.O.T. SAFETY CHAINS PLATFORM IN TONGUE FOR PUMP (5) HOSE STORAGE HOOKS (4) 6" WIDE CROSS MEMBERS (2) 12" X 12" FILL STEPS CONSPICUITY TAPE



Available Options

- FREE-BACKING HYDRAULIC SURGE BRAKES
- ELECTRIC BRAKES WITH SAFETY BREAKAWAY KIT
- BALL COUPLER OR LUNETTE EYE
- WELDED-ON FENDERS
- HOSE STAND
- INDUCTOR STAND
- 5' FRAME EXTENSION

Tire Options

- 11L X 22.5 HIGHWAY TIRES

